



Trilo SG 400

• Vacuum Sweeping • Scarifying • Mowing

www.trilo.com



Verticutting and vacuum sweeping at the same time.



Flailshaft with twisted flails.



Scarifier with flailblades.



Trilo SG 400 with gulley brush and dust suppression kit.



Trilo SG 400 vacuum sweeper

The Trilo Vacuum Sweeper SG 400 is your reliable friend for tackling the most challenging jobs with ease. It has been specifically designed for clearing open areas such as golf courses, parks, sports and show grounds of leaves, litter and grass cuttings. The SG 400 has a high capacity fan giving it a high work rate and a working width of 1.5 or 1.7 m. The balanced fan wheel and the double walled casing provide a wear resistant, reliable and above all a safe source of power. The impeller casing has an inspection trap in the lower part. A large assortment of auxiliary tools such as a scarifier, several brush rollers, a flailmower, gulley brushes and a 5+1 metres long hand held wander hose make the SG 400 suitable for a versatile use all the year round.

The Trilo SG 400 is a compact machine having big tyres, which makes it perfectly suitable for use at places where manoeuvrability and low ground pressure are required. A relatively small tractor can be used to form an efficient, compact and economical combination with the machine. To cope with the amount of material collected in a 4 m³ container, the machine also features a 2 m high tip facility meaning it can unload into the back of a truck or skip, keeping downtime to minimum.

The optional double-walled top cover exhausts the airflow downwards at the rear of the machine. At the same time the air is filtered by a coarse filter net.

The main advantage is: suppression of dust clouds especially in urban environments, on top of that reduction in sound levels and at the rear the runover grass will be erected caused by the firm, controlled airflow.

Technical specifications

- | | | | |
|-----------------|-------------|------------------|-------------------|
| ● Working width | : 1.5/1.7 m | ● PTO | : 540 rpm/min. |
| ● Height | : 2.05 m | ● Hydraulics | : 1 double acting |
| ● Length | : 4.50 m | ● Tipping height | : 2 meter |
| ● Width | : 1.70 m | ● Container | : 4 cubic meter |
| ● Weight | : 1300 kg | ● Turbine | : Ø 850 mm |
| ● Tires | : 15 x17 | ● Hp requirement | : > 31 kW-45 Hp |

Options:

- Flexible scarifier 1.7 meter, 3 mm thick blades with 30 mm blade spacing
- Flailshaft with twisted flails
- Scarifier with flail blades, 3 mm thick blades with 30 mm blade spacing
- Wide tires 19 x 17
- Wanderhose Ø 200 x 5 metres
- Dust suppression kit
- Gulley brush



Vanmac

Astronaut 40
 NL - 3824 MJ Amersfoort
 Tel.: (+31) (0)33 456 45 50
 Fax: (+31) (0)33 456 44 33
 E-mail: sales@trilo.com
 Internet: www.trilo.com